

View Online at <https://aerobasegroup.com/nsn/4320-01-259-9166>

**Mounting Type:**

Flange

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded external

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded external

**Drive Connection Type:**

Close coupled

**Maximum Discharge Flow Rate:**

2.2 gallons per minute

**Operating Speed At Rated Capacity:**

1725.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Rotation Direction:**

Clockwise

**Rotary Pump Design:**

Gear

**Operation Method:**

Powered

**Drive Shaft Type:**

D-type

**Drive Shaft End Diameter:**

0.250 inches

**Pump Basic Material:**

Bronze

**Discharge Connection Thread Size And Series/type Designator:**

0.250-18 npt

**Intake Connection Thread Size And Series/type Designator:**

0.250-18 npt

**Special Features:**

Use 1/3 hp mtr; liq pumped must be clear, non-flammable & non-corrosive to brz; self priming; buna n lip seal; c bearings; stls stl shaft; temp range -40 degrees f to +210 degrees f

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400