

View Online at <https://aerobasegroup.com/nsn/4320-01-260-0573>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Oil

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Watertight

Pump Quantity:

1

Cooling Method:

Water cooled

Maximum Discharge Flow Rate:

43.0 gallons per minute

Total Head:

5.000 feet and 19.250 feet

Operating Speed At Rated Capacity:

1550.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Impeller Quantity:

1

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

7.7

Discharge Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Voltage In Volts:

115.0

Phase:

Single

Special Features:

End item: force provide (army)

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400