

View Online at <https://aerobasegroup.com/nsn/4320-01-260-3302>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Stage Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**Maximum Discharge Flow Rate:**

66.6 gallons per minute and 15.0 gallons per minute

**Discharge Pressure:**

1.3 pounds per square inch gage

**Total Head:**

5.000 feet and 20.000 feet

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Axial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Double

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

2.1

**Discharge Connection Thread Size And Series/type Designator:**

1.250-11-1/2 npt

**Prime Mover Power Rating:**

0.33 horsepower

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

Sump depth 26-17/32 in., min sump diameter 21 in; plastic float w/stainless steel rod; bronze impeller; threaded stainless steel shaft; brass pipe; cast bronze base, volute; 8ft 3-conductor cord, plug

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400