

View Online at <https://aerobasegroup.com/nsn/4320-01-261-9747>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Cylinder Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Unthreaded external

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Unthreaded external

**Current Type:**

Ac

**Media For Which Designed:**

Sewage and water, fresh

**Pump Quantity:**

1

**Pumping Element Type:**

Diaphragm

**Cooling Method:**

Blower cooled

**Maximum Discharge Flow Rate:**

0.02 gallons per minute

**Discharge Pressure:**

125.0 pounds per square inch gage

**Pumping Element Operating Position:**

Horizontal

**Pump Reciprocating Design:**

Single acting

**Reciprocating Stroke Type:**

Variable

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

6.4

**Prime Mover Power Rating:**

0.05 horsepower

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

Acrylic casing, hypalon valve seats, polytetrafluoroethylene gaskets; fully adj output by dial control; maximum temp 125 degrees f; incl 4ft vinyl sution hose, 8ft polyethylene discharge tube, foot valve, strainer and back check valve w/ 1/2 in. Mpt pipe fittings; also for pollution control, chemical and acid appl

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400