

View Online at <https://aerobasegroup.com/nsn/4320-01-261-9747>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Cylinder Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Unthreaded external

Discharge Connection Quantity:

1

Discharge Connection Type:

Unthreaded external

Current Type:

Ac

Media For Which Designed:

Sewage and water, fresh

Pump Quantity:

1

Pumping Element Type:

Diaphragm

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

0.02 gallons per minute

Discharge Pressure:

125.0 pounds per square inch gage

Pumping Element Operating Position:

Horizontal

Pump Reciprocating Design:

Single acting

Reciprocating Stroke Type:

Variable

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

6.4

Prime Mover Power Rating:

0.05 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Acrylic casing, hypalon valve seats, polytetrafluoroethylene gaskets; fully adj output by dial control; maximum temp 125 degrees f; incl 4ft vinyl sution hose, 8ft polyethylene discharge tube, foot valve, strainer and back check valve w/ 1/2 in. Mpt pipe fittings; also for pollution control, chemical and acid appl

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400