NSN 4320-01-263-2983

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-263-2983

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Intake Connection Quantity:
1 Intelle Connection Times
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1 Dischause Composition Tomas
Discharge Connection Type:
Round flange
Current Type:
Ac
Media For Which Designed:
Hydrocarbon fuels and oils
Pump Quantity:
1
End Application:
Power rotary pump unit; imo ind.Inc.; w/s 170 ft patrol coastal (pc-1)
Maximum Discharge Flow Rate:
215.0 gallons per minute
Discharge Pressure:
47.0 pounds per square inch gage
Suction Lift:
11.000 feet
Operating Speed At Rated Capacity:
1750.0 revolutions per minute
Operation Relationship Design:
Simultaneous
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Prime Mover Power Rating:
15.0 horsepower
Voltage In Volts:
440.0
Phase:
Three
Frequency In Hertz:

60.0

NSN 4320-01-263-2983

Rotary Pump Unit - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400