NSN 4320-01-266-1365

Rotary Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-266-1365

Intoka Connection Quantity		
Intake Connection Quantity:		
2 Intoka Connection Type:		
Intake Connection Type:		
Rectangular flange		
Discharge Connection Quantity:		
2 Disabase Consortion Toron		
Discharge Connection Type:		
Rectangular flange		
Drive Connection Type:		
Flexible coupled		
Media For Which Designed:		
Hydrocarbon fuels and oils		
Maximum Discharge Flow Rate:		
7.5 gallons per minute		
Discharge Pressure:		
1000.0 pounds per square inch gage		
Operating Speed At Rated Capacity:		
1800.0 revolutions per minute		
Pump Rotation Direction:		
Clockwise		
Volume Control Type:		
Pressure compensation		
Control Location:		
Center		
Rotary Pump Design:		
Vane		
Operation Method:		
Powered		
Drive Shaft Type:		
Machine keyway		
Drive Shaft End Diameter:		
0.750 inches		
Drive Shaft Length:		
1.250 inches		
Unpackaged Unit Length:		
8.990 inches		
Unpackaged Unit Width:		
10.940 inches		
Unpackaged Unit Height:		
4.880 inches		
Pump Basic Material:		

Steel

NSN 4320-01-266-1365

Rotary Pump - Page 2 of 2



	Specia	I Features
--	--------	------------

2 pumps, close coupled with a single drive shaft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400