

View Online at <https://aerobasegroup.com/nsn/4320-01-268-4448>

Current Type:

Ac

Media For Which Designed:

Water, salt

Environmental Protection:

Submersible

Pump Quantity:

1

Maximum Discharge Flow Rate:

200.0 gallons per minute

Total Head:

70.000 feet

Suction Lift:

20.000 feet

Centrifugal Pump Impeller Quantity:

1

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Criticality Code Justification:

Feat

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Items are being coded as critical to insure source inspection will be performed at the point of manufacture, prior to material receipt by the us navy or other dod components. These items are piece parts or end items in support of vital military hardware necessary to sustain the successful mission of the ships, submarines, and shore stations of the us navy. Critical features including, but not limited to, dimensions, tolerances/clearances, electronic characteristics, and metallurgical properties will bespecified for government q ar (quality assurance representatives) to insure the highest possible degree of quality and reliability of these parts being delivered under navicp contracts

Frequency In Hertz:

60.0

Specification Or Standard:

1 class

Departure From Cited Document:

Magnetic permeability shall not exceed 2.0 after fabrication

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: