

View Online at <https://aerobasegroup.com/nsn/4320-01-270-5834>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Oil

Stage Quantity:

1

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Sewage

Environmental Protection:

Watertight

Pump Quantity:

1

Cooling Method:

Water cooled

Maximum Discharge Flow Rate:

43.0 gallons per minute

Total Head:

5.000 feet

Operating Speed At Rated Capacity:

1550.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Axial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Unpackaged Unit Width:

10.2500 inches

Unpackaged Unit Height:

9.750 inches

Pump Basic Material:

Bronze

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

8.0

Discharge Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

0.333 horsepower

Voltage In Volts:

115.0

Phase:

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400