

View Online at <https://aerobasegroup.com/nsn/4320-01-275-4208>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, fresh

Pump Quantity:

1

End Application:

Low pressure steam drain transfer pump model cv-62

Maximum Discharge Flow Rate:

50.0 gallons per minute

Discharge Pressure:

110.0 pounds per square inch gage

Total Head:

55.000 feet

Operating Speed At Rated Capacity:

3600.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

5.84

Prime Mover Power Rating:

3.450 horsepower

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Drip-proof; thermal overload and undervoltage protection

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400