

View Online at <https://aerobasegroup.com/nsn/4320-01-275-8009>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, distilled

Pump Quantity:

1

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

110.0 gallons per minute

Discharge Pressure:

70.0 pounds per square inch gage

Total Head:

143.000 feet

Operating Speed At Rated Capacity:

3545.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Unpackaged Unit Length:

31.750 inches

Unpackaged Unit Width:

17.7500 inches

Unpackaged Unit Height:

17.438 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

16.9

Prime Mover Power Rating:

10.000 horsepower

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Specification Data:

81349-mil-p-17840b government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400