

View Online at <https://aerobasegroup.com/nsn/4320-01-282-4658>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Cubic Measure:

4.0000 cubic feet

End Application:

Used on make-up feed pump onboard 378 whec hull numbers 715, 716, 718 and721 coast guard vessels

Maximum Discharge Flow Rate:

20.0 gallons per minute

Total Head:

50.000 feet

Operating Speed At Rated Capacity:

1800.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

2.1

Prime Mover Power Rating:

1.5 horsepower

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400