NSN 4320-01-287-0107

Rotary Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-287-0107

Manustina Tuna
Mounting Type:
Flange
Intake Connection Quantity:
1 Intelle Compation Type:
Intake Connection Type:
Rectangular flange
Discharge Connection Quantity:
Discharge Connection Type:
Rectangular flange
Drive Connection Type:
Close coupled
Media For Which Designed:
Hydrocarbon fuels and oils
End Application:
Used on cargo handling equipment onboard 180 wlb coast guard vessels
Maximum Discharge Flow Rate:
47.0 gallons per minute
Discharge Pressure:
2000.0 pounds per square inch gage
Operating Speed At Rated Capacity:
1800.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Pump Rotation Direction:
Clockwise
Rotary Pump Design:
Gear
Operation Method:
Powered
Drive Shaft Type:
Splined, involute external
Drive Shaft End Diameter:
1.248 inches
Drive Shaft Length:
1.380 inches
Special Features:
Port size left side 1.5000 inches; right side 1.250 inches; input shaft 13 splines type 1saeb
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4320-01-287-0107

Rotary Pump - Page 2 of 2



Demi			

No

Fiig:

A19400