NSN 4320-01-287-2482

Rotary Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-287-2482

Mounting Type:						
Base						
Intake Connection Quantity:						
1						
Intake Connection Type:						
Threaded external						
Discharge Connection Quantity:						
1						
Discharge Connection Type:						
Threaded external						
Drive Connection Type:						
Rigid coupled						
Media For Which Designed:						
Hydrocarbon fuels and oils						
Maximum Discharge Flow Rate:						
38.5 gallons per minute						
Discharge Pressure:						
150.0 pounds per square inch gage						
Operating Speed At Rated Capacity:						
1800.0 revolutions per minute						
Pumping Element Operating Position:						
Horizontal						
Pump Rotation Direction:						
Clockwise						
Rotary Pump Design:						
Gear						
Operation Method:						
Powered						
Drive Shaft Type:						
Woodruff keyway						
Drive Shaft End Diameter:						
1.000 inches						
Drive Shaft Length:						
2.250 inches						
Unpackaged Unit Length:						
14.312 inches						
Unpackaged Unit Width:						
7.000 inches						
Unpackaged Unit Height:						
6.188 inches						
Pump Basic Material:						

Iron

NSN 4320-01-287-2482

Rotary Pump - Page 2 of 2



Discharge Co	1! '	TI I	O: AI	0! //	D! 1
i jischarde (./	nnection	Inread	SIZE ANA	Series/type	Designator

1.500-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Special Features:

Viscosities 5000 ssu; gears and shaft hardened steel; bearings bronze; mech seal; 212.0 degrees f max; self-priming

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A19400