

View Online at <https://aerobasegroup.com/nsn/4320-01-288-0794>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Frame

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Water, salt

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**End Application:**

Buffalo pump inc. Series 8x10 slv air conditioning circulating pump

**Maximum Discharge Flow Rate:**

1575.0 gallons per minute

**Discharge Pressure:**

25.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

1750.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

67.74

**Prime Mover Power Rating:**

40.0 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Special Features:**

Rotation clockwise

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400