

View Online at <https://aerobasegroup.com/nsn/4320-01-290-4952>

Mounting Type:

Base

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Drive Connection Type:

Rigid coupled

Maximum Discharge Flow Rate:

4.6 gallons per minute and 4.5 gallons per minute and 4.4 gallons per minute and 4.2 gallons per minute

Discharge Pressure:

20.0 pounds per square inch gage and 50.0 pounds per square inch gage and 100.0 pounds per square inch gage and 200.0 pounds per square inch gage

Suction Lift:

17.000 feet

Operating Speed At Rated Capacity:

900.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Pump Rotation Direction:

Clockwise and counterclockwise

Rotary Pump Design:

Gear

Operation Method:

Powered

Drive Shaft Type:

Machine keyway

Drive Shaft End Diameter:

0.562 inches

Drive Shaft Length:

1.375 inches

Unpackaged Unit Length:

6.250 inches

Unpackaged Unit Width:

2.750 inches

Unpackaged Unit Height:

3.688 inches

Pump Basic Material:

Bronze

Discharge Connection Thread Size And Series/type Designator:

0.375-18 npt

Intake Connection Thread Size And Series/type Designator:

0.375-18 npt

Special Features:

Grease fittings furnished

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400