NSN 4320-01-293-5109

Rotary Pump - Page 1 of 2

Intake Connection Quantity:

Mounting Type:

Flange

2



View Online at https://aerobasegroup.com/nsn/4320-01-293-5109

2
Discharge Connection Type:
Threaded internal and threaded internal
Drive Connection Type:
Rigid coupled
Media For Which Designed:
Hydrocarbon fuels and oils
Maximum Discharge Flow Rate:
35.5 gallons per minute and 30.0 gallons per minute
Discharge Pressure:
3000.0 pounds per square inch gage
Operating Speed At Rated Capacity:
2800.0 revolutions per minute and 3100.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Pump Rotation Direction:
Counterclockwise
Rotary Pump Design:
Gear
Operation Method:
Powered
Drive Shaft Type:
Splined, involute external
Drive Shaft Length:
1.690 inches
Unpackaged Unit Length:
13.280 inches
Unpackaged Unit Width:
5.750 inches
Unpackaged Unit Height:
5.350 inches
Discharge Connection Thread Size And Series/type Designator:
1.062-12 un and 1.062-12 un
Intake Connection Thread Size And Series/type Designator:
1.062-12 un
Special Features:
Tandem pump; flange sae 2-bolt, 6.880in.W, 4.000in.H; shaft 7/8in 13 tooth
Supplementary Features:
Second suction port plugged

NSN 4320-01-293-5109

Rotary Pump - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400