

View Online at <https://aerobasegroup.com/nsn/4320-01-293-5109>

**Mounting Type:**

Flange

**Intake Connection Quantity:**

2

**Discharge Connection Type:**

Threaded internal and threaded internal

**Drive Connection Type:**

Rigid coupled

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Maximum Discharge Flow Rate:**

35.5 gallons per minute and 30.0 gallons per minute

**Discharge Pressure:**

3000.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

2800.0 revolutions per minute and 3100.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Rotation Direction:**

Counterclockwise

**Rotary Pump Design:**

Gear

**Operation Method:**

Powered

**Drive Shaft Type:**

Splined, involute external

**Drive Shaft Length:**

1.690 inches

**Unpackaged Unit Length:**

13.280 inches

**Unpackaged Unit Width:**

5.750 inches

**Unpackaged Unit Height:**

5.350 inches

**Discharge Connection Thread Size And Series/type Designator:**

1.062-12 un and 1.062-12 un

**Intake Connection Thread Size And Series/type Designator:**

1.062-12 un

**Special Features:**

Tandem pump; flange sae 2-bolt, 6.880in.W, 4.000in.H; shaft 7/8in 13 tooth

**Supplementary Features:**

Second suction port plugged

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400