
# NSN 4320-01-294-8790

Centrifugal Pump Unit - Page 1 of 2





Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Intake Connection Quantity:

1

### Intake Connection Type:

Threaded internal

**Discharge Connection Quantity:** 

1

#### **Discharge Connection Type:**

Threaded internal

**Current Type:** 

Ac

#### Media For Which Designed:

## Water, fresh

Environmental Protection:

Dripproof

## Pump Quantity:

1

Cooling Method:

Air to air cooled

### Maximum Discharge Flow Rate:

35.0 gallons per minute

### **Operating Speed At Rated Capacity:**

3500.0 revolutions per minute

## Pumping Element Operating Position:

Horizontal

#### **Centrifugal Pump Design:**

Mixed flow

## Centrifugal Pump Impeller Quantity:

1

## Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

# Discharge Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

## Intake Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Prime Mover Power Rating:

7.5 horsepower

# NSN 4320-01-294-8790

Centrifugal Pump Unit - Page 2 of 2

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A19400

