

View Online at <https://aerobasegroup.com/nsn/4320-01-298-3291>

**Thread Direction:**

Right-hand and right-hand and right-hand

**Torque Load Rating:**

55.4 inch-pounds

**Mounting Type:**

Face

**Keyway Width:**

0.250 inches

**Keyway Depth:**

0.125 inches

**Thread Size:**

9/16-18 and 7/8-14 and 7/8-14

**Shaft Diameter:**

1.000 inches

**Operating Speed At Rated Capacity In Rpm:**

1500.0

**Keyway Length:**

1.688 inches

**Drive Shaft Type:**

Machine keyway

**Housing Material:**

Iron

**Screw Thread Series Designator:**

Unf and unf and unf

**Shaft Rotation Direction:**

Clockwise and counterclockwise

**Thread Location:**

Internal and internal and internal

**Shaft Protrusion Length:**

2.000 inches

**Connection Quantity:**

1 and 1 and 1

**Connection Type:**

Outlet

**Maximum Working Pressure Rating At Specificationified Temperature Range:**

3000psi at minus 40 degrees f to plus 160 degrees f

**Connection Design:**

Threaded and threaded and threaded

**Displacement Type:**

Constant or variable

**Constant Displacement Per Revolution:**

3.500 cubic inches

**Connection Government Specification/std:**

And10050-6; and10050-10; and10050-10

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T103-f