

View Online at <https://aerobasegroup.com/nsn/4320-01-298-3291>

Thread Direction:

Right-hand and right-hand and right-hand

Torque Load Rating:

55.4 inch-pounds

Mounting Type:

Face

Keyway Width:

0.250 inches

Keyway Depth:

0.125 inches

Thread Size:

9/16-18 and 7/8-14 and 7/8-14

Shaft Diameter:

1.000 inches

Operating Speed At Rated Capacity In Rpm:

1500.0

Keyway Length:

1.688 inches

Drive Shaft Type:

Machine keyway

Housing Material:

Iron

Screw Thread Series Designator:

Unf and unf and unf

Shaft Rotation Direction:

Clockwise and counterclockwise

Thread Location:

Internal and internal and internal

Shaft Protrusion Length:

2.000 inches

Connection Quantity:

1 and 1 and 1

Connection Type:

Outlet

Maximum Working Pressure Rating At Specificationified Temperature Range:

3000psi at minus 40 degrees f to plus 160 degrees f

Connection Design:

Threaded and threaded and threaded

Displacement Type:

Constant or variable

Constant Displacement Per Revolution:

3.500 cubic inches

Connection Government Specification/std:

And10050-6; and10050-10; and10050-10

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T103-f