

View Online at <https://aerobasegroup.com/nsn/4320-01-301-9098>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Cylinder Quantity:

1

Intake Connection Quantity:

4

Intake Connection Type:

Threaded external

Discharge Connection Quantity:

4

Discharge Connection Type:

Threaded external

Current Type:

Ac

Environmental Protection:

Fungus proof

Pump Quantity:

4

Pumping Element Type:

Diaphragm

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

0.172 liters per minute

Discharge Pressure:

100.0 pounds per square inch gage

Pumping Element Operating Position:

Vertical

Pump Reciprocating Design:

Single acting

Reciprocating Stroke Type:

Variable

Volume Control Type:

Rotary

Control Location:

Center

Operation Relationship Design:

Simultaneous

Unpackaged Unit Length:

16.300 inches

Unpackaged Unit Width:

9.500 inches

Unpackaged Unit Height:

16.880 inches

Pump Basic Material:

Iron

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

4.8 and 2.4

Discharge Connection Thread Size And Series/type Designator:

0.750-16 unf

Intake Connection Thread Size And Series/type Designator:

0.750-16 unf

Prime Mover Power Rating:

0.333 horsepower

Voltage In Volts:

115.0 and 230.0

Phase:

Single

Special Features:

Inlet and outlet fittings to retain 0.250 in. Id by 0.500 in. Od hose

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400