

View Online at <https://aerobasegroup.com/nsn/4320-01-301-9098>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Cylinder Quantity:**

1

**Intake Connection Quantity:**

4

**Intake Connection Type:**

Threaded external

**Discharge Connection Quantity:**

4

**Discharge Connection Type:**

Threaded external

**Current Type:**

Ac

**Environmental Protection:**

Fungus proof

**Pump Quantity:**

4

**Pumping Element Type:**

Diaphragm

**Cooling Method:**

Blower cooled

**Maximum Discharge Flow Rate:**

0.172 liters per minute

**Discharge Pressure:**

100.0 pounds per square inch gage

**Pumping Element Operating Position:**

Vertical

**Pump Reciprocating Design:**

Single acting

**Reciprocating Stroke Type:**

Variable

**Volume Control Type:**

Rotary

**Control Location:**

Center

**Operation Relationship Design:**

Simultaneous

**Unpackaged Unit Length:**

16.300 inches

**Unpackaged Unit Width:**

9.500 inches

**Unpackaged Unit Height:**

16.880 inches

**Pump Basic Material:**

Iron

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

4.8 and 2.4

**Discharge Connection Thread Size And Series/type Designator:**

0.750-16 unf

**Intake Connection Thread Size And Series/type Designator:**

0.750-16 unf

**Prime Mover Power Rating:**

0.333 horsepower

**Voltage In Volts:**

115.0 and 230.0

**Phase:**

Single

**Special Features:**

Inlet and outlet fittings to retain 0.250 in. Id by 0.500 in. Od hose

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400