

View Online at <https://aerobasegroup.com/nsn/4320-01-304-8205>

**Cylinder Quantity:**

2

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Drive Connection Type:**

Close coupled

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Pumping Element Type:**

Piston

**End Application:**

2420-01-196-0299pallet transporter

**Maximum Discharge Flow Rate:**

20.0 gallons per minute

**Discharge Pressure:**

2000.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

1800.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Rotation Direction:**

Clockwise

**Pump Reciprocating Design:**

Single acting

**Reciprocating Stroke Type:**

Variable

**Volume Control Type:**

Pressure compensation

**Drive Shaft Type:**

Machine keyway

**Drive Shaft End Diameter:**

1.250 inches

**Drive Shaft Length:**

1.910 inches

**Unpackaged Unit Length:**

11.620 inches

**Unpackaged Unit Width:**

8.8800 inches

**Unpackaged Unit Height:**

7.440 inches

**Discharge Connection Thread Size And Series/type Designator:**

1.625-12 un

**Intake Connection Thread Size And Series/type Designator:**

1.625-12 un

**Special Features:**

Pressure compensator 250/3000psi

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400