NSN 4320-01-305-5812

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-305-5812

Prime Mover Quantity:
1
Stage Quantity:
1
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded external
Current Type:
Ac
Media For Which Designed:
Sewage or water, fresh
Pump Quantity:
1
Maximum Discharge Flow Rate:
89.0 gallons per minute
Total Head:
10.000 feet
Operating Speed At Rated Capacity:
1725.0 revolutions per minute
Pumping Element Operating Position:
Vertical
Centrifugal Pump Design:
Mixed flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Current Rating In Amps:
10.4 and 5.2
Discharge Connection Thread Size And Series/type Designator:
2.000-11-1/2 npt
Features Provided:
Self-priming
Prime Mover Power Rating:
0.5 horsepower
Voltage In Volts:
445.0 and 220.0

115.0 and 230.0

NSN 4320-01-305-5812

Centrifugal Pump Unit - Page 2 of 2



P	haea.	
г	nase.	

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400