

View Online at <https://aerobasegroup.com/nsn/4320-01-312-0309>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Frame

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Liquid

Pump Quantity:

1

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

10.0 gallons per minute

Discharge Pressure:

100.0 pounds per square inch gage

Operating Speed At Rated Capacity:

1200.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Gear

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

4.9 and 2.5

Discharge Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Prime Mover Power Rating:

1.5 horsepower

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400