

View Online at <https://aerobasegroup.com/nsn/4320-01-312-0309>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Frame

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Liquid

**Pump Quantity:**

1

**Cooling Method:**

Blower cooled

**Maximum Discharge Flow Rate:**

10.0 gallons per minute

**Discharge Pressure:**

100.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

1200.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Rotary Pump Design:**

Gear

**Operation Relationship Design:**

Simultaneous

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

4.9 and 2.5

**Discharge Connection Thread Size And Series/type Designator:**

1.500-11-1/2 npt

**Intake Connection Thread Size And Series/type Designator:**

1.500-11-1/2 npt

**Prime Mover Power Rating:**

1.5 horsepower

**Voltage In Volts:**

230.0 and 460.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400