NSN 4320-01-313-4185

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-313-4185

| Prime Mover Quantity: |
|---|
| 1 |
| Stage Quantity: |
| 1 |
| Intake Connection Quantity: |
| 1 |
| Intake Connection Type: |
| Oval flange |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Oval flange |
| Current Type: |
| Ac |
| Media For Which Designed: |
| Water, fresh |
| Environmental Protection: |
| Dripproof |
| Pump Quantity: |
| 1 |
| Maximum Discharge Flow Rate: |
| 115.0 gallons per minute |
| Total Head: |
| 23.000 feet |
| Operating Speed At Rated Capacity: |
| 1725.0 revolutions per minute |
| Pumping Element Operating Position: |
| Horizontal |
| Centrifugal Pump Design: |
| Radial flow |
| Centrifugal Pump Impeller Quantity: |
| 1 |
| Centrifugal Pump Impeller Suction Type: |
| Single |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| Current Rating In Amps: |
| 30.0 |
| Prime Mover Power Rating: |
| 0.500 horsepower |

NSN 4320-01-313-4185

Centrifugal Pump Unit - Page 2 of 2

A19400



| Voltage In Volts: |
|---|
| 230.0 and 460.0 |
| Phase: |
| Three |
| Special Features: |
| Magnetic starter, manual reset button and thermal overload protectors |
| Frequency In Hertz: |
| 60.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |