NSN 4320-01-314-7801

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-314-7801

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Current Type:
Dc
Media For Which Designed:
Hydrocarbon fuels and oils
Pump Quantity:
1
Cooling Method:
Air to air cooled
Maximum Discharge Flow Rate:
0.3 gallons per minute
Discharge Pressure:
50.0 pounds per square inch gage
Operating Speed At Rated Capacity:
2250.0 revolutions per minute
Pumping Element Operating Position:
Vertical
Rotary Pump Design:
Gear
Operation Relationship Design:
Simultaneous
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Current Rating In Amps:
20.0
Discharge Connection Thread Size And Series/type Designator:
0.437-20 unf
Intake Connection Thread Size And Series/type Designator:

0.437-20 unf

NSN 4320-01-314-7801

Rotary Pump Unit - Page 2 of 2



Vم	ltage	In \	/ol	lts:
vu	ILAUE		<i>,</i> 0	ILO.

24.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400