

View Online at <https://aerobasegroup.com/nsn/4320-01-316-0124>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**Maximum Discharge Flow Rate:**

175.0 gallons per minute

**Discharge Pressure:**

175.0 pounds per square inch gage

**Total Head:**

85.000 feet

**Operating Speed At Rated Capacity:**

3500.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Operation Relationship Design:**

Simultaneous

**Unpackaged Unit Length:**

22.250 inches

**Unpackaged Unit Width:**

18.0000 inches

**Unpackaged Unit Height:**

5.500 inches

**Pump Basic Material:**

Iron

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Open

**Current Rating In Amps:**

17.9 and 16.2 and 8.1

**Prime Mover Power Rating:**

5.0 horsepower

**Voltage In Volts:**

208.0 and 230.0 and 460.0

**Phase:**

Three

**Special Features:**

125lb ansi flanged ports, 2in.-size discharge, 2 1/2in.-size suction

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400