

View Online at <https://aerobasegroup.com/nsn/4320-01-316-1002>

**Mounting Type:**

Flange

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Rectangular flange

**Discharge Connection Quantity:**

2

**Discharge Connection Type:**

Threaded internal and threaded internal

**Media For Which Designed:**

Hydrocarbon fuels and oils

**End Application:**

Hydraulic power unit, control general inc., part number 8733, used in the ship control system onboard 210 ft wmec coast guard vessels

**Maximum Discharge Flow Rate:**

6.2 gallons per minute and 1.7 gallons per minute

**Discharge Pressure:**

2000.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

1200.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Pump Rotation Direction:**

Clockwise

**Rotary Pump Design:**

Vane

**Operation Method:**

Powered

**Drive Shaft Type:**

Machine keyway

**Drive Shaft End Diameter:**

Between 0.874 inches and 0.875 inches

**Drive Shaft Length:**

1.940 inches

**Discharge Connection Thread Size And Series/type Designator:**

1.0625-12 un and 0.750-16 unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400