NSN 4320-01-317-3572

Centrifugal Pump - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-01-317-3572

Media For Which Designed: Liquid End Application: Power and hand pumps Maximum Discharge Flow Rate: 500.0 gallons per minute Discharge Pressure: 17.3 pounds per square inch gage Operating Speed At Rated Capacity: 1765.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Centrifugal Pump Design: Mixed flow
End Application: Power and hand pumps Maximum Discharge Flow Rate: 500.0 gallons per minute Discharge Pressure: 17.3 pounds per square inch gage Operating Speed At Rated Capacity: 1765.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Centrifugal Pump Design:
End Application: Power and hand pumps Maximum Discharge Flow Rate: 500.0 gallons per minute Discharge Pressure: 17.3 pounds per square inch gage Operating Speed At Rated Capacity: 1765.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Centrifugal Pump Design:
Power and hand pumps Maximum Discharge Flow Rate: 500.0 gallons per minute Discharge Pressure: 17.3 pounds per square inch gage Operating Speed At Rated Capacity: 1765.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Centrifugal Pump Design:
Maximum Discharge Flow Rate: 500.0 gallons per minute Discharge Pressure: 17.3 pounds per square inch gage Operating Speed At Rated Capacity: 1765.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Centrifugal Pump Design:
500.0 gallons per minute Discharge Pressure: 17.3 pounds per square inch gage Operating Speed At Rated Capacity: 1765.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Centrifugal Pump Design:
Discharge Pressure: 17.3 pounds per square inch gage Operating Speed At Rated Capacity: 1765.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Centrifugal Pump Design:
17.3 pounds per square inch gage Operating Speed At Rated Capacity: 1765.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Centrifugal Pump Design:
Operating Speed At Rated Capacity: 1765.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Centrifugal Pump Design:
1765.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Centrifugal Pump Design:
Pumping Element Operating Position: Horizontal Pump Rotation Direction: Clockwise Centrifugal Pump Design:
Horizontal Pump Rotation Direction: Clockwise Centrifugal Pump Design:
Pump Rotation Direction: Clockwise Centrifugal Pump Design:
Clockwise Centrifugal Pump Design:
Centrifugal Pump Design:
Mixed flow
WILCO HOW
Centrifugal Pump Impeller Suction Type:
Single
Special Features:
6.5 bhp, 9.50 in diameter impeller, 5.00 in suction, 5.00 in discharge, mechanical seal
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A19400