

View Online at <https://aerobasegroup.com/nsn/4320-01-318-6359>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Environmental Protection:

Watertight

Pump Quantity:

1

Cooling Method:

Blower cooled

End Application:

Aviation defueling pump

Maximum Discharge Flow Rate:

50.0 gallons per minute

Discharge Pressure:

15.0 pounds per square inch gage

Suction Lift:

1.250 feet

Operating Speed At Rated Capacity:

520.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Vane

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

2.9

Prime Mover Power Rating:

2.000 horsepower

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400