

View Online at <https://aerobasegroup.com/nsn/4320-01-319-7800>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

10.8 gallons per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Unpackaged Unit Length:

12.312 inches

Unpackaged Unit Width:

5.6250 inches

Unpackaged Unit Height:

6.375 inches

Pump Basic Material:

Bronze

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Current Rating In Amps:

2.16

Discharge Connection Thread Size And Series/type Designator:

0.375-18 npt

Intake Connection Thread Size And Series/type Designator:

0.375-18 npt

Prime Mover Power Rating:

0.33 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Item equipped with motor

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400