NSN 4320-01-320-2892

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-320-2892

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Ac
Media For Which Designed:
Water, distilled
Pump Quantity:
1
Cooling Method:
Air to air cooled
End Application:
Power and hand pumps
Maximum Discharge Flow Rate:
5.0 gallons per minute
Discharge Pressure:
30.0 pounds per square inch gage
Suction Lift:
69.000 feet
Operating Speed At Rated Capacity:
3580.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Axial flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Prime Mover Type:
Electric motor

NSN 4320-01-320-2892

Centrifugal Pump Unit - Page 2 of 2



Inclosure Type:
Fully enclosed
Prime Mover Power Rating:
2.0 horsepower
Voltage In Volts:
440.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A19400