

View Online at <https://aerobasegroup.com/nsn/4320-01-321-9961>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air and water, fresh

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded external

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded external

Current Type:

Ac

Environmental Protection:

Submersible

Pump Quantity:

1

Cooling Method:

Water-air cooled

End Application:

3610-01-165-5688

Maximum Discharge Flow Rate:

3.3 gallons per minute

Total Head:

5.000 feet

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Unpackaged Unit Length:

4.500 inches

Unpackaged Unit Width:

5.0000 inches

Unpackaged Unit Height:

5.000 inches

Pump Basic Material:

Plastic

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

0.7

Discharge Connection Thread Size And Series/type Designator:

0.250-18 npt

Intake Connection Thread Size And Series/type Designator:

0.500-14 npt

Prime Mover Power Rating:

0.01 horsepower

Voltage In Volts:

115.0

Phase:

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400