NSN 4320-01-322-9165

Rotary Pump Unit - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4320-01-322-9165



Prime Mover Quantity:

1

Mounting Type:

Base

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Pump Quantity:

1

Maximum Discharge Flow Rate:

2.8 gallons per minute

Discharge Pressure:

50.0 pounds per square inch gage

Suction Lift:

13.000 feet

Operating Speed At Rated Capacity:

1175.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Gear

Operation Relationship Design:

Independent

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

0.8

Discharge Connection Thread Size And Series/type Designator:

0.500-14 npt

Intake Connection Thread Size And Series/type Designator:

0.500-14 npt

NSN 4320-01-322-9165

Rotary Pump Unit - Page 2 of 2



Prime Mover Power Rating:

0.5 horsepower

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400