NSN 4320-01-323-1723

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-323-1723

Prime Mover Quantity:
1
Mounting Type:
Base
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Media For Which Designed:
Sewage and water, salt
Pump Quantity:
1
Maximum Discharge Flow Rate:
12.0 gallons per minute
Discharge Pressure:
22.0 pounds per square inch gage
Suction Lift:
15.000 feet
Operating Speed At Rated Capacity:
3450.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Axial flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Prime Mover Type:
Electric motor
Discharge Connection Thread Size And Series/type Designator:
1.875-12 unf
Intake Connection Thread Size And Series/type Designator:
1.875-12 unf
Features Provided:
Self-priming

NSN 4320-01-323-1723

Centrifugal Pump Unit - Page 2 of 2



_			-		
C	hο	14		.ife	•
•			_	.116	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400