

View Online at <https://aerobasegroup.com/nsn/4320-01-324-9177>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**Maximum Discharge Flow Rate:**

170.0 gallons per minute

**Discharge Pressure:**

175.0 pounds per square inch gage

**Total Head:**

28.000 feet

**Operating Speed At Rated Capacity:**

3500.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Operation Relationship Design:**

Simultaneous

**Unpackaged Unit Length:**

16.688 inches

**Unpackaged Unit Width:**

8.3750 inches

**Unpackaged Unit Height:**

8.750 inches

**Pump Basic Material:**

Bronze

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Open

**Current Rating In Amps:**

5.4 and 4.9 and 2.4

**Discharge Connection Thread Size And Series/type Designator:**

1.500-11-1/2 npt

**Intake Connection Thread Size And Series/type Designator:**

2.000-11-1/2 npt

**Prime Mover Power Rating:**

1.5 horsepower

**Voltage In Volts:**

208.0 and 230.0 and 460.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400