

View Online at <https://aerobasegroup.com/nsn/4320-01-329-4635>

Mounting Type:

Flange

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Drive Connection Type:

Close coupled

Media For Which Designed:

Hydrocarbon fuels and oils

End Application:

Firetruck; kovatch corp, model p22/p24

Maximum Discharge Flow Rate:

11.0 gallons per minute

Discharge Pressure:

100.0 pounds per square inch gage

Operating Speed At Rated Capacity:

1200.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Pump Rotation Direction:

Counterclockwise

Rotary Pump Design:

Vane

Operation Method:

Powered

Drive Shaft Type:

Threaded and woodruff keyway

Drive Shaft End Diameter:

0.938 inches

Drive Shaft Length:

2.781 inches

Discharge Connection Thread Size And Series/type Designator:

1.062-12 un

Intake Connection Thread Size And Series/type Designator:

1.625-12 un

Special Features:

Outlet port inline w/inlet; 6.0 gpm, 1750.0 psi relief valve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400