

View Online at <https://aerobasegroup.com/nsn/4320-01-329-4635>

**Mounting Type:**

Flange

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Drive Connection Type:**

Close coupled

**Media For Which Designed:**

Hydrocarbon fuels and oils

**End Application:**

Firetruck; kovatch corp, model p22/p24

**Maximum Discharge Flow Rate:**

11.0 gallons per minute

**Discharge Pressure:**

100.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

1200.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Rotation Direction:**

Counterclockwise

**Rotary Pump Design:**

Vane

**Operation Method:**

Powered

**Drive Shaft Type:**

Threaded and woodruff keyway

**Drive Shaft End Diameter:**

0.938 inches

**Drive Shaft Length:**

2.781 inches

**Discharge Connection Thread Size And Series/type Designator:**

1.062-12 un

**Intake Connection Thread Size And Series/type Designator:**

1.625-12 un

**Special Features:**

Outlet port inline w/inlet; 6.0 gpm, 1750.0 psi relief valve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400