NSN 4320-01-331-1690

Rotary Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-331-1690

Manustina Tomas
Mounting Type:
Flange
Intake Connection Quantity:
1 Intelle Connection Type:
Intake Connection Type:
Rectangular flange
Discharge Connection Quantity:
Discharge Connection Type:
Threaded internal
Drive Connection Type:
Rigid coupled
Media For Which Designed:
Hydrocarbon fuels and oils
End Application:
John deere model 755bcrawler loader
Maximum Discharge Flow Rate:
17.0 gallons per minute
Discharge Pressure:
100.0 pounds per square inch gage
Operating Speed At Rated Capacity:
1200.00 revolutions per minute
Pumping Element Operating Position:
Horizontal
Pump Rotation Direction:
Counterclockwise
Rotary Pump Design:
Gear
Operation Method:
Powered
Drive Shaft Type:
Splined, involute internal
Pump Basic Material:
Iron
Discharge Connection Thread Size And Series/type Designator:
1.312-12 un
Special Features:
Viton seals; inlet 4-bolt 1.50in.Dia; dbl shaft seal; mtg flange sae-b 2-bolt
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4320-01-331-1690

Rotary Pump - Page 2 of 2



Demilitarization:

No

Fiig:

A19400