

View Online at <https://aerobasegroup.com/nsn/4320-01-334-8088>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Bell mouth

Discharge Connection Quantity:

1

Discharge Connection Type:

Unthreaded external

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

10.0 gallons per minute

Discharge Pressure:

5.2 pounds per square inch gage

Total Head:

1.000 feet

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Unpackaged Unit Length:

9.000 inches

Unpackaged Unit Width:

4.5000 inches

Unpackaged Unit Height:

4.500 inches

Pump Basic Material:

Plastic

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

0.6

Features Provided:

Self-priming

Prime Mover Power Rating:

0.033 horsepower

Voltage In Volts:

230.0

Phase:

Single

Special Features:

Total head 9.0 ft at 2.98 gpm; automatic shutoff at 12.0 ft

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400