NSN 4320-01-336-6005

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-336-6005

| Prime Mover Quantity: |
|---|
| 1 |
| Mounting Type: |
| Base |
| Stage Quantity: |
| 1 |
| Intake Connection Quantity: |
| 1 |
| Intake Connection Type: |
| Round flange |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Round flange |
| Current Type: |
| Ac |
| Media For Which Designed: |
| Liquid |
| Pump Quantity: |
| 1 |
| Cooling Method: |
| Blower cooled |
| Maximum Discharge Flow Rate: |
| 1125.0 gallons per minute |
| Discharge Pressure: |
| 80.0 pounds per square inch gage |
| Total Head: |
| 205.000 feet |
| Operating Speed At Rated Capacity: |
| 1790.0 revolutions per minute |
| Pumping Element Operating Position: |
| Horizontal |
| Centrifugal Pump Design: |
| Axial flow |
| Centrifugal Pump Impeller Quantity: |
| 1 |
| Centrifugal Pump Impeller Suction Type: |
| Single |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Prime Mover Type: Electric motor |

Fully enclosed

NSN 4320-01-336-6005 Centrifugal Pump Unit - Page 2 of 2



| Current Rating In Amps: |
|--------------------------------|
| 120.0 |
| Prime Mover Power Rating: |
| 100.0 horsepower |
| Voltage In Volts: |
| 440.0 |
| Phase: |
| Three |
| Frequency In Hertz: |
| 60.0 |
| Supplementary Features: |
| Chilled water pump |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A19400 |