

View Online at <https://aerobasegroup.com/nsn/4320-01-337-4021>

**Mounting Type:**

Flange

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Rectangular flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Rectangular flange

**Drive Connection Type:**

Close coupled

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Maximum Discharge Flow Rate:**

51.333 gallons per minute

**Discharge Pressure:**

3000.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

2800.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Rotation Direction:**

Clockwise

**Rotary Pump Design:**

Vane

**Operation Method:**

Powered

**Drive Shaft Type:**

Key type, internal

**Drive Shaft Length:**

2.810 inches

**Unpackaged Unit Length:**

9.170 inches

**Unpackaged Unit Width:**

5.320 inches

**Unpackaged Unit Height:**

5.320 inches

**Special Features:**

Qflanged inlet port 1.50in.Dia, 4 mtg holes 1/2-13unc-2b x 0.88in.Dp located 1.406in. By 2.750i. Apart; flanged outlet port 1.00in.Dia, 4 mtg holes 3/8-16unc-2b x 0.750in.Dp; mtg flange sae-b 2 bolt w/ pilot boss recess

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400