NSN 4320-01-339-0398

Rotary Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-339-0398

Mounting Type:
Flange
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Drive Connection Type:
Rigid coupled
Media For Which Designed:
Hydrocarbon fuels and oils
Maximum Discharge Flow Rate:
4.76 gallons per minute
Discharge Pressure:
3000.0 pounds per square inch gage
Operating Speed At Rated Capacity:
6000.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Pump Rotation Direction:
Pump Rotation Direction:
Pump Rotation Direction: Clockwise
Pump Rotation Direction: Clockwise Rotary Pump Design:
Pump Rotation Direction: Clockwise Rotary Pump Design: Gear
Pump Rotation Direction: Clockwise Rotary Pump Design: Gear Operation Method:
Pump Rotation Direction: Clockwise Rotary Pump Design: Gear Operation Method: Powered
Pump Rotation Direction: Clockwise Rotary Pump Design: Gear Operation Method: Powered Drive Shaft Type:
Pump Rotation Direction: Clockwise Rotary Pump Design: Gear Operation Method: Powered Drive Shaft Type: Key type, external
Pump Rotation Direction: Clockwise Rotary Pump Design: Gear Operation Method: Powered Drive Shaft Type: Key type, external Drive Shaft End Diameter:
Pump Rotation Direction: Clockwise Rotary Pump Design: Gear Operation Method: Powered Drive Shaft Type: Key type, external Drive Shaft End Diameter: 0.500 inches
Pump Rotation Direction: Clockwise Rotary Pump Design: Gear Operation Method: Powered Drive Shaft Type: Key type, external Drive Shaft End Diameter: 0.500 inches Drive Shaft Length:
Pump Rotation Direction: Clockwise Rotary Pump Design: Gear Operation Method: Powered Drive Shaft Type: Key type, external Drive Shaft End Diameter: 0.500 inches Drive Shaft Length: 0.750 inches
Pump Rotation Direction: Clockwise Rotary Pump Design: Gear Operation Method: Powered Drive Shaft Type: Key type, external Drive Shaft End Diameter: 0.500 inches Drive Shaft Length: 0.750 inches Unpackaged Unit Length:
Pump Rotation Direction: Clockwise Rotary Pump Design: Gear Operation Method: Powered Drive Shaft Type: Key type, external Drive Shaft End Diameter: 0.500 inches Drive Shaft Length: 0.750 inches Unpackaged Unit Length: 3.690 inches
Pump Rotation Direction: Clockwise Rotary Pump Design: Gear Operation Method: Powered Drive Shaft Type: Key type, external Drive Shaft End Diameter: 0.500 inches Drive Shaft Length: 0.750 inches Unpackaged Unit Length: 3.690 inches Unpackaged Unit Width:
Pump Rotation Direction: Clockwise Rotary Pump Design: Gear Operation Method: Powered Drive Shaft Type: Key type, external Drive Shaft End Diameter: 0.500 inches Drive Shaft Length: 0.750 inches Unpackaged Unit Length: 3.690 inches Unpackaged Unit Width: 2.670 inches
Pump Rotation Direction: Clockwise Rotary Pump Design: Gear Operation Method: Powered Drive Shaft Type: Key type, external Drive Shaft End Diameter: 0.500 inches Drive Shaft Length: 0.750 inches Unpackaged Unit Length: 3.690 inches Unpackaged Unit Width: 2.670 inches Unpackaged Unit Height:

NSN 4320-01-339-0398

Rotary Pump - Page 2 of 2



Discharge Connection Thread Size And Series/type Designator:
0.562-18 un
Intake Connection Thread Size And Series/type Designator:
0.750-16 un
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A19400