

View Online at <https://aerobasegroup.com/nsn/4320-01-343-3650>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Flange

Stage Quantity:

3

Intake Connection Quantity:

1

Intake Connection Type:

Rectangular flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Rectangular flange

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

45.0 gallons per minute

Total Head:

6.000 feet

Operating Speed At Rated Capacity:

1725.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Prime Mover Power Rating:

250.0 horsepower

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400