

View Online at <https://aerobasegroup.com/nsn/4320-01-344-8470>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Cubic Measure:

0.0104 cubic feet

End Application:

Used onboard 180 ft coast guard vessels

Maximum Discharge Flow Rate:

180.0 gallons per minute

Total Head:

60.000 feet

Operating Speed At Rated Capacity:

3600.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

13.1

Discharge Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Prime Mover Power Rating:

5.0 horsepower

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400