

View Online at <https://aerobasegroup.com/nsn/4320-01-345-5137>

Thread Direction:

Right-hand and left-hand and right-hand

Torque Load Rating:

4040.0 inch-pounds or 5040.0 inch-pounds

Spline Major Diameter:

1.000 inches

Mounting Type:

Flange

Mounting Hole Diameter:

Between 0.529 inches and 0.536 inches

Mounting Hole Quantity:

4

Thread Size:

0.875 and 0.875 and 0.438

Operating Speed At Rated Capacity In Rpm:

477.0 or 720.0

Mounting Bolt Circle Diameter:

5.000 inches

End Application:

Paccar/braden carco, ahs3/ahsu3 hyd winch

Drive Shaft Type:

Splined, involute external

Screw Thread Series Designator:

Unf and unf and unf

Shaft Rotation Direction:

Clockwise and counterclockwise

Thread Location:

Internal and internal and internal

Connection Quantity:

1 and 1 and 1

Connection Type:

Inlet and outlet and drain

Maximum Working Pressure Rating At Specificationified Temperature Range:

2500psi at 180deg f

Connection Design:

Threaded and threaded and threaded

Displacement Type:

Constant or variable

Constant Displacement Per Revolution:

9.600 cubic inches

Special Features:

Two speed 9.6/4.8ci; 18gpm; bearingless; sae 6b splined shaft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T103-f