

View Online at <https://aerobasegroup.com/nsn/4320-01-345-5137>

**Thread Direction:**

Right-hand and left-hand and right-hand

**Torque Load Rating:**

4040.0 inch-pounds or 5040.0 inch-pounds

**Spline Major Diameter:**

1.000 inches

**Mounting Type:**

Flange

**Mounting Hole Diameter:**

Between 0.529 inches and 0.536 inches

**Mounting Hole Quantity:**

4

**Thread Size:**

0.875 and 0.875 and 0.438

**Operating Speed At Rated Capacity In Rpm:**

477.0 or 720.0

**Mounting Bolt Circle Diameter:**

5.000 inches

**End Application:**

Paccar/braden carco, ahs3/ahsu3 hyd winch

**Drive Shaft Type:**

Splined, involute external

**Screw Thread Series Designator:**

Unf and unf and unf

**Shaft Rotation Direction:**

Clockwise and counterclockwise

**Thread Location:**

Internal and internal and internal

**Connection Quantity:**

1 and 1 and 1

**Connection Type:**

Inlet and outlet and drain

**Maximum Working Pressure Rating At Specificationified Temperature Range:**

2500psi at 180deg f

**Connection Design:**

Threaded and threaded and threaded

**Displacement Type:**

Constant or variable

**Constant Displacement Per Revolution:**

9.600 cubic inches

**Special Features:**

Two speed 9.6/4.8ci; 18gpm; bearingless; sae 6b splined shaft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T103-f